

LUBRICATING OIL COMPOSITION

Patent number: JP2003041283
Publication date: 2003-02-13
Inventor: ISHIMARU MITSUAKI; SATO TAKASHI
Applicant: NIPPON OIL CORP
Classification:
- International: C10M129/10; C10M129/54; C10M133/56; C10M135/10; C10M135/18; C10M137/02; C10M137/10; C10M139/00; C10M139/06; C10M159/22; C10M159/24; C10M169/04; C10M137/04; C10M129/00; C10M133/00; C10M135/00; C10M137/00; C10M139/00; C10M159/00; C10M169/00; (IPC1-7): C10M169/04; C10M129/10; C10M129/54; C10M133/56; C10M135/10; C10M135/18; C10M137/02; C10M137/04; C10M137/10; C10M139/00; C10M159/22; C10M159/24; C10N10/04; C10N10/12; C10N30/00; C10N30/04; C10N30/06; C10N40/04; C10N40/25
- european:
Application number: JP20010232827 20010731
Priority number(s): JP20010232827 20010731

BEST AVAILABLE COPY

Report a data error here

Abstract of JP2003041283

PROBLEM TO BE SOLVED: To provide a lubricating oil composition which excels in fuel consumption saving performance at middle and high temperatures and, in addition, excels in wet clutch friction properties. **SOLUTION:** The lubrication oil composition comprises a base oil and, based on the total weight of the composition, (A) 0.003-0.1 mass%, in terms of Mo element, organomolybdenum compound, (B) 0.08-0.3 mass%, in terms of N element, boron-containing succinimide and/or boron-free succinimide at a mass ratio of component (B) in terms of N element to component (A) in terms of Mo element of ≥ 1.6 , (C) 0.01-0.16 mass%, in terms of an alkaline earth metal, alkaline earth metal-based cleaning agent, (D) 0.01-0.1 mass%, in terms of zinc element, zinc dithiophosphate, (E) ≤ 0.1 mass%, in terms of phosphorus element, phosphoric (phosphorous) esters and, simultaneously, with a sulfate ash in the composition of ≤ 1 mass%.

Data supplied from the esp@cenet database - Worldwide